

16 fiber HD LC-HD LC

Feature

- ◆ SENKO Uniboot LC for Hi-density connectivity
- ◆ Connector with Pull tab for easy installation
- ◆ Low insertion loss



Specifications

End A (LC)	Dust Cap Color	Connector Type	Connector Color	Boot Type	Boot Color
	Beige or Customized	LC/UPC LC/APC LC/PC	Blue Green Aqua Violet Lime Green	Standard	Beige
End B (LC)	Dust Cap Color	Connector Type	Connector Color	Boot Type	Boot Color
	Beige or Customized	LC/UPC LC/APC LC/PC	Blue Green Aqua Violet Lime Green	Standard	Beige
Cable	Fiber Type	Cable Type	Cable OD	Jacket Color	Jacket Material
	SM G657A2 9/125 MM OM3 50/125 MM OM4 50/125 MM OM5 50/125	Round	3.0mm	Yellow Aqua Violet Lime Green	LSZH

Technical Data

Fiber Type	Connector Type	Insertion Loss	Return Loss	Repeatability	Durability	Operating temperature
SM	UPC	$\leq 0.2\text{dB}$	$\geq 55\text{dB}$	$\leq 0.2\text{dB}$	> 500	-20~75℃
	APC		$\geq 65\text{dB}$			
MM	PC	$\leq 0.1\text{dB}$	/			

Address: Room 302,3rd Floor,C building Dakan technology garden
Dakan village,Xili town,Nanshan district,Shenzhen city,China

Tel: +86-0755-86330891
Fax: +86-0755-86330896